



ESTORES DECORATIVOS
MOTORES

Catálogo de Productos



TM 35 – 8/12



Type	Voltage (V/Hz)	Power (W)	Current (A)	Speed (rpm)	Torque (Nm)	Working Time (min.)	Insulation Class	Protetion Class	Max (circle)	Cable Length (m)	Overall Dimension (mm)	Noise Level (dB)
TM35-3/26	230/50	150	0,65	26	3	4	F	P44	26	1,5	4G 0,75	≤46
TM45-6/12	230/50	150	0,65	12	6	4	F	P44	26	1,5	4G 0,75	≤46
TM45-8/12	230/50	150	0,65	12	8	4	F	P44	26	1,5	4G 0,75	≤46

TM 45 – 10/17D



Type	Voltage (V/Hz)	Power (W)	Current (A)	Speed (rpm)	Torque (Nm)	Working Time (min.)	Insulation Class	Protetion Class	Max (circle)	Cable Length (m)	Overall Dimension (mm)	Noise Level (dB)
TMW45-10/17D	230/50	230	1,0	17	10	4	F	P44	28	1,5	4G 0,75	≤48
TMW45-20/17D	230/50	270	1,2	17	20	4	F	P44	28	1,5	4G 0,75	≤48
TMW45-30/17D	230/50	300	1,3	17	30	4	F	P44	28	1,5	4G 0,75	≤52
TMW45-40/12D	230/50	300	1,3	12	40	4	F	P44	28	1,5	4G 0,75	≤52

TM 45 – 10/17



Type	Voltage (V/Hz)	Power (W)	Current (A)	Speed (rpm)	Torque (Nm)	Working Time (min.)	Insulation Class	Protetion Class	Max (circle)	Cable Length (m)	Overall Dimension (mm)	Noise Level (dB)
TMN45-10/17	230/50	230	1,0	17	10	4	F	P44	18	1,5	3G 0,75	≤48
TMN45-20/17	230/50	270	1,2	17	20	4	F	P44	18	1,5	3G 0,75	≤48
TMN45-30/17	230/50	300	1,3	17	30	4	F	P44	18	1,5	3G 0,75	≤52
TMN45-40/12	230/50	300	1,3	12	40	4	F	P44	18	1,5	3G 0,75	≤52

TM 45R – 20/17



Type	Voltage (V/Hz)	Power (W)	Current (A)	Speed (rpm)	Torque (Nm)	Working Time (min.)	Insulation Class	Protetion Class	Max (circle)	Cable Length (m)	Overall Dimension (mm)	Noise Level (dB)
TM45-10/17R	230/50	230	1,0	17	10	4	F	P44	18	1,5	3G 0,75	≤48
TM45-20/17R	230/50	270	1,2	17	20	4	F	P44	18	1,5	3G 0,75	≤48
TM45-30/17R	230/50	300	1,3	17	30	4	F	P44	18	1,5	3G 0,75	≤52
TM45-40/12R	230/50	300	1,3	12	40	4	F	P44	18	1,5	3G 0,75	≤52

TM 45 - 30/17S

(RECURSO MANUAL)



Type	Voltage (V/Hz)	Power (W)	Current (A)	Speed (rpm)	Torque (Nm)	Working Time (min.)	Insulation Class	Protection Class	Max (circle)	Cable Length (m)	Overall Dimension (mm)	Noise Level (dB)
TM45-10/17S	230/50	230	1,0	17	10	4	F	P44	20	1,5	4G 0,75	≤48
TM45-20/17S	230/50	270	1,2	17	20	4	F	P44	18	1,5	4G 0,75	≤48
TM45-30/17S	230/50	300	1,3	17	30	4	F	P44	18	1,5	4G 0,75	≤52
TM45-40/17S	230/50	300	1,3	12	40	4	F	P44	18	1,5	4G 0,75	≤52

TM 59 - 90/12

(CAPACIDADE + 100KG)



Type	Voltage (V/Hz)	Power (W)	Current (A)	Speed (rpm)	Torque (Nm)	Working Time (min.)	Insulation Class	Protection Class	Max (circle)	Cable Length (m)	Overall Dimension (mm)	Noise Level (dB)
TM59-60/12	230/50	370	1,6	12	60	4	F	P44	18	1,5	3G 0,75	≤56
TM59-70/12	230/50	410	1,8	12	70	4	F	P44	18	1,5	3G 0,75	≤56
TM59-80/12	230/50	410	1,8	12	80	4	F	P44	18	1,5	3G 0,75	≤56
TM59-90/12	230/50	500	2,2	12	90	4	F	P44	18	1,5	3G 0,75	≤56
TM59-100/12	230/50	500	2,2	12	100	4	F	P44	18	1,5	3G 0,75	≤56





MOTORES FERA

Comércio e Venda de Estores e Automatismos, Lda.

Morada

Rua do Negral, 985
4440-115 Campo – Valongo

Telf. 224152395/6

Fax. 224152397

E-mail - motoresfera@sapo.pt

Site – www.motoresfera.pt

GPS: 41° 10' 41. 21" N 8° 26' 42, 53" 0